

Retracement of the W. bdy. of T 34 N, R 22 E, Mt. Diablo B. and M.

Chains.

82.03 The cor. of Tps. 34 and 35 N, Rs. 21 and 22 E, a basalt stone, firmly set in the ground; marked, witnessed and of the dimensions described by the Surveyor General. I destroy all traces of this corner and its accessories and reestablish it at the same point as follows; Set a basalt stone 30-10-7 ins., 20 ins. in the ground for cor. of Tps. 34 and 35 N, R 21 E, on W. bdy. of T 34 N, R 22 E, marked 34 N on S.W. and 21 E on N.W. face and with 6 notches on N. and W. edges. Raise a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor.

Pits impracticable.

Land, rolling.

Soil, rocky. 4th. rate

Vegetation, sage brush and bunchgrass.

N 0°6'E bet. secs. 31 and 36. T35N Rgs. 21 & 22 E.

Ascending over rolling land.

40.00 The 1-4 sec. cor., a basalt stone, firmly set in the ground; marked, witnessed and of the dimensions described by the Surveyor General.

Land, rolling.

Soil, rocky. 4th. rate.

Vegetation, sagebrush and bunchgrass.

August 3, 1910.

Subdivision of T 34 N, R 22 E, Mt. Diablo B. and M.

Aug. 8, 1910.

I begin at the S. bdy. of the Tp., at the corner of secs. 1, 2, 35 and 36. This corner was established by me August 4, 1910.

Thence I run

N 0°1'W bet. secs. 35 and 36

Ascending steep, rocky mountains.

16.35 Mountain spur, slopes S. W. Thence across rocky mountain slope.

40.00 Set a granite stone 16-10-6 ins., 12 ins. in the ground for 1-4 sec. cor., marked 1-4 on the N. face and raise