

Resurvey of Subdivisions of T 22 N R 23 E.

Chains.

May 30th. 1.00P.M.1910.

N. 89° 37' E bet. secs. 6 and 7.

8.87 Ridge, bears N. and S.

38.94 The old 1/4 sec. cor. bet. secs. 6 and 7.

An andesite stone 18x8x6 ins. in a mound of stone, marked 1/4 on N. face. I destroy all traces of the old cor. and in the same place I set an andesite stone 18x8x6 ins. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face; and raise a mound of stone 2 ft. base 1 1/2 ft. high N. of cor.

Pits impracticable.

I continue my measurement, but change course to, N. 89° 39' E.

41.87 Canon, course SE.

47.87 Spur, bears N. and S.

53.87 Coal canon and creek, 6 lks. wide 12 ins. deep, course NE

77.87 The ^{old} cor. of secs. 5, 6, 7 and 8. A basalt stone 18x8x8 ins. in a mound of stone, marked with 5 notches on the S. and 5 notches on the E. edge; I destroy all traces of the old cor. and in the same place I set a basalt stone 18x8x8 ins. 12 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, marked with 5 notches on the S. and 5 notches on the E. edge; and raise a mound of stone 2 ft. base 1 1/2 ft. high W. of cor.

Pits impracticable.

Land, mountainous.

Soil, rocky 4th. rate.

Timber, cedar, mahogany and sagebrush.

Mountainous land 77.87 chs.

See Supplemental Notes, Book "F"