

## Resurvey of East boundary of T 31 N. R 23 E.

Chains.

Land, level.

Soil, sandy loam 1st. rate.

Timber, sagebrush.

Level land, 79.94 chs.

N. Co ~~15'~~<sup>18'</sup> W. bet. secs. 19 and 24.

- 10.00 Wagon road, bears SE and NW.
- 51.55 Wagon road ; bears SW. and NE.
- 40.32 The old  $\frac{1}{4}$  sec. cor. A stake 3 ins. square almost decayed marked  $\frac{1}{4}$  on face and lying in a small mound of earth. I destroy all traces of the old cor. and in the same place I set an andesite stone 12x8x6 ins. 8 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on W. face; dig pits 18x18x12 ins. N. and S. of stone 3 ft. dist. and raise a mound of earth  $3\frac{1}{2}$  ft. base  $1\frac{1}{2}$  ft, high W. of cor.
- 47.03 Intersect the closing cor. on the line of the Pyramid lake Indian reservation at 11.57 chs. S:20<sup>o</sup> 45' E. from the 135 M. cor. which is a basalt stone 14x10x10 ins. above ground marked C C on the S. P. L. I R on the ~~W.~~<sup>N</sup> face, with a mound of earth  $3\frac{1}{2}$  ft. base  $1\frac{1}{2}$  ft. high S. of cor.
- 82.12 The point established at the intersection of section lines I set an andesite stone 12x10x10 ins. 8 ins. in the ground for the cor. of secs. 13, 18, 19 and 24, marked with 3 grooves on the S. and 3 grooves on the N. face; dig pits 18x18x12 ins. in each sec.  $5\frac{1}{2}$  ft. dist. and raise a mound of earth, 4 ft. base 3 ft. high W. of cor.
- Land, level.
- Soil, sandy loam 1st. rate.
- Timber, sagebrush.
- Level land, 82.68 chs.

Resurvey of Subdivisions of T. 31 N. R 23 E.

West bet. secs. 13 and 24.

- 13.92 Intersect the closing cor. of Pyramid lake Indian reservation at 51.49 chs. S. 20<sup>o</sup> 45' E. of 134 M. cor., which is a basalt stone 12x10x10 ins. above ground, marked C C on the W. P. L. I R on the ~~W.~~<sup>E</sup> face with a mound of earth  $3\frac{1}{2}$  ft base  $1\frac{1}{2}$  ft. high W. of cor.