

Resurvey of Subdivisions of T 21 N. R 23 E.

Chains.	N. to 35' W. bet. secs. 11 and 12.
2.35	Wagon road, bears NE. and SW.
15.80	Draw, course SE.
40.85½	Set an andesite stone 18x9x5 ins. 12 ins. in the ground for ¼ sec. cor. marked ¼ on W. face and raise a mound of stone 2 ft. base 1½ ft. high W. of cor. Pits impracticable.
42.15	Draw, course E.
59.25	Draw, course E.
81.71	The old cor. of secs. 1, 3, 11, and 12. An andesite stone 10x10x 7 ins. above ground marked with 5 notches on the S. and 1 notch on the E. edge, with a mound of stone 2 ft base 1½ ft. high W. of cor. Land, rolling. Soil, stony, 3rd. rate. Timber, sagebrush. Rolling land, 81.71 chs.
N. bet. secs. 1 and 2.	
6.00	Ridge, bears E. and W.
11.64	Draw, course SE.
30.75	Intersect the closing cor. on the line of the Pyramid Lake Indian Reservation, at 132 M. 17.75 chs. A basalt stone 16x12x10 ins. above ground marked CC on the S. and P L I R on the <sup>N</sup> face with a mound of stone 3 ft. base 1½ ft. high S. of cor. Reservation line bears S. 20o45' E.
36.00	Draw, course E.
40.00	Set a basalt stone 16x12x10 ins. 11 ins. in the ground for ¼ sec. cor. marked ¼ on W. face and raise a mound of stone 2 ft. base 1½ ft. high W. of cor. Pits impracticable.
41.30	Draw, course E.
44.00	Ridge, bears E. and W.
83.44	Set a basalt stone 20x10x8 ins. 15 ins. in the ground for cor. of secs. 1, 2, 35 and 36, marked with 1 groove on the E and 5 grooves on the W. face, and raise a mound