

## Resurvey of Subdivisions of T. 22 N R 23 E.

Chains.

marked with 5 notches on the S. and  
 5 notches on the E. edge, in a mound of stones. I destroy  
 all traces of the old cor. and in the same place I set  
 an andesite stone 18x8x8 ins. 12 ins. in the ground for  
 cor. of secs. 5, 6, 7, and 8, marked with 5 notches on the  
 S and 5 notches on the E. edge and raise a mound of stone  
 2 ft. base 1½ ft. high W. of cor. Pits impracticable.  
 Land, mountainous.  
 Soil, stony, 3rd. rate.  
 Timber, cedar and sagebrush.  
 Mountainous land 75.64 chs.

---

S 89° 39' W. bet. secs. 6 and 7.

24.00 Coal canon and creek, 8 lks wide 12 ins deep, course NE.  
 30.00 Spur, bears N. and S.  
 36.00 Canon, course SE.  
 38.93 The old ¼ sec. cor. bet. secs. 6 and 7. An andesite stone  
 18x8x6 ins. lying near a pile of stone, marked ¼ on face.  
 I destroy all traces of the old cor. and in the same  
 place I set an andesite stone 18x8x6 ins. 12 ins. in the  
 ground for ¼ sec. cor. marked ¼ on N. face and raise a  
 mound of stone 2 ft, base 1½ ft, high N. of cor.  
 Pits impracticable.  
 Change course to S 89° 37' W. continuing measurement.  
 69.00 Ridge, bears N. and S.  
 77.87 The cor of secs. 1, 6, 7 and 12. An andesite stone, 15 x 10  
 x 8 ins. in a mound of stone, marked with 1 groove on  
 the N. and 5 grooves on the S. face. I destroy all traces  
 of the old cor. and in the same place I set an andesite  
 stone 15x10x8 ins. 10 ins. in the ground for cor. of  
 secs. 1, 6, 7 and 12. marked with 1 groove on the N. and  
 5 grooves on the S. face;  
 From which,  
 A cedar 8 ins. dia. bears S 46° W. 28 lks dist.  
 marked T 22 N R 22 E S 12 B T.