

Second Standard Parallel South, through Range 65 East,

Chains

$$\begin{array}{r} 534 \\ \frac{1}{4} \\ \hline 1911 \end{array}$$

and dig pits, $18 \times 18 \times 12$ ins., east and west of cor., 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor., N. 12 lks. from the tangent.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of secs. 34 and 35, with brass cap mkd.

$$\begin{array}{r|l} T85 & R65E \\ \hline 534 & 535 \\ \hline 1911 \end{array}$$

and dig pits, $24 \times 18 \times 12$ ins., crosswise on each line, E. and W. 3 ft., and N. of cor. 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, N. of cor.

Land, level.
Soil, sandy loam; 1st rate.
No timber.

S. $89^{\circ}56'E$, on the tangent, S. of sec. 35
Over level land, through bunch grass and scattering chaparral.

40.00 N. 15.5 lks. from the tangent.
Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} 535 \\ \frac{1}{4} \\ \hline 1911 \end{array}$$

and dig pits, $18 \times 18 \times 12$ ins., east and west of cor., 3 ft. dist.; and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

70.50 Wash, 1 ch. wide, drains south.

80.00 N. 19 lks. from the tangent.
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for standard cor. of secs. 35 and 36, with brass cap mkd.

$$\begin{array}{r|l} T85 & R65E \\ \hline 535 & 536 \\ \hline 1911 \end{array}$$