

Second Standard Parallel South, through Range 65 East.

Shanis.

and dig pits, $24 \times 18 \times 12$ ins, crosswise on each line, E. and W. 3 ft., and N. of cor. 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, N. of cor.

Land, level.

Soil, sandy loam; 1st rate.

No timber.

May 28, 1911

May 29, 1911

S. $89^{\circ} 55' E.$ on the tangent, S. of sec. 36

Over level land, through bunch grass and chaparral.

7.00 Enter wash; drains S. $44^{\circ} W.$

11.00 Leave wash; drains S. $44^{\circ} W.$

25.00 Leave valley, bears N. $44^{\circ} E.$ about 6 miles and S. $44^{\circ} W.$ about 20 miles; leave bunch grass; enter rocky, mountainous land; ascend rapidly.

40.00 N. 23 lks. from the tangent.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bed rock, in mound of stone, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd. 536

$\frac{1}{4}$
1911

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

72.00 Point of spur, 150 ft. above valley, projects N.; descend abruptly.

79.00 Head of gulch, 100 ft. below spur, drains N. $60^{\circ} W.$; ascend abruptly

80.00 N. 27 lks. from the tangent.

Set an iron post, 3 ft. long, 3 in. diam., 12 ins. in the ground to bed rock, in mound of stone, for standard cor. of Tps. 8 S., Rgs. 65 and 66 E., with brass cap mkd.

T 85

R 65 E | R 66 E

536 | 531

1911

and raise a mound of stone; 2 ft. base