

Second Standard Parallel South, through Range 67 East

Chains

T85	R67 E
535	536

1911

and raise a mound of stone, 2 ft. base,
1 1/2 ft. high, N. of cor.

Land, rolling.

Soil, gravelly and rocky; 4th rate
No timber

N. 89° 55' E. on the tangent, S. of sec. 36

Over rough, rolling land, through scattering
shadscale, chaparral and yohua; ascend2.75 Spur, 120 ft. above ravine, projects S. 30° W.;
descend20.00 Head of ravine, 20 ft. below spur, drains S. 40° W.;
ascend30.00 Spur, 40 ft. above ravine, projects S. 40° W.;
descend39.00 Ravine, 25 ft. below spur, drains S. 35° W.;
ascend.

40.00 N. 23 lks. from the tangent.

Set an iron post, 3 ft. long, 1 in. diam., 24 ins.
in the ground, for standard 1/4 sec. cor.,
with brass cap mkd.

536

1/4

1911

and raise a mound of stone, 2 ft. base,
1 1/2 ft. high, N. of cor.

52.00 Spur, 100 ft. above ravine, projects S. 41° W.;
descend.62.60 Ravine, 50 ft. below spur, drains S. 43° W.;
ascend.73.00 Spur, 75 ft. above ravine, projects S. 44° W.;
descend79.00 Ravine, 40 ft. below spur, drains S. 35° W.;
ascend

80.00 N. 27 lks. from the tangent.

Set an iron post, 3 ft. long, 3 in. diam., 24 ins.
in the ground, for standard cor. of Tpo.
S. S., Rgs. 67 and 68 E., with brass cap