

Second Standard Parallel South, through Range 70 East,

- Chains S. 89° 50' E., on the tangent, S. of sec. 35
Over rolling land, through shadescale and scattering
Joshua and chaparral; descend
- 23.00 Wash, 25 ft. below spur, chains S. 46° E.;
ascend
- 26.90 Small spur, 20 ft. above wash, projects S. 40° E.;
descend
- 36.00 Small wash, 25 ft. below spur, chains N. 10° E.;
ascend gradually.
- 40.00 N. 83 lks. from the tangent
Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in
the ground, for standard 1/4 sec. cov., with
brass cap mkd.

535

1/4

1911

- and raise a mound of stone, 2 ft. base,
1 1/2 ft. high, N. of cov.
- 80.00 N. 91 lks. from the tangent.
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins.
in the ground, for standard cov. of secs. 35
and 36, with brass cap mkd.

T 85 | R 70 E

535 | 536

1911

and dig pits, 24 x 18 x 12 ins., crosswise on
each side, E. and W. 3 ft., and N. of cov. 7
ft. dist.; and raise a mound of earth,
4 ft. base, 2 ft. high, N. of cov.
Land, rolling.
Soil, gravelly and rocky; 4th rate.
No timber

Aug. 9, 1911

- Aug. 10, 1911.
S. 89° 49' E. on the tangent, S. of sec. 36.
Over rolling land, through shadescale and
scattering Joshua and chaparral.
- 40.00 N. 100.5 lks. from the tangent.
Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in
the ground, for standard 1/4 sec. cov., with