

Subdivision of T. 9 S., R. 67 E.

- Chains descend
 72.00 Ravine, 75 ft. below spur, drains S. 40° W.;
 ascend
 77.80 Spur, 100 ft. above ravine, projects S. 45° W.;
 descend
 78.80 Intersect the Second Standard Parallel
 South 26.93 chs. West of the St. cov. of
 secs. 35 and 36, which I established
 July 19, 1911
 At my point of intersection
 Set an iron post, 3 ft. long, 3 in. diam., 24 in.
 in the ground, for closing cov. of secs.
 1 and 2, with brass cap marked

| | |
|--------------|----|
| C | C |
| 52 | 51 |
| T 9 S R 67 E | |
| 1911 | |

and raise a mound of stone, 2 ft. base,
 1 1/2 ft. high, S. of cov.
 Land, rolling.
 Soil, gravelly and rocky; 4th rate.
 No timber.

July 21, 1911

- July 5, 1911
 Run the cov. of secs. 2, 3, 34 and 35, on S. ldy.
 of Tp., which I established June 26,
 1911, from
 N. 0° 01' W., bet. secs. 34 and 35
 Over rolling land, through scattering shad-
 scale, chaparral and Joshua; ascend.
 7.80 Spur, 100 ft. above sec. cov., projects N. 80° W.;
 descend
 19.00 Ravine, 150 ft. below spur, drains N. 75° W.;
 ascend
 24.60 Spur, 170 ft. above ravine, projects N. 80° W.;
 descend
 39.00 Gulch, 175 ft. below spur, drains N. 52° W.;
 ascend over small ledges
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 9 in. in
 the ground to hard pan, in mound