

## Subdivision of T. 9 S., R. 67 E.

Chains  
and 4th rate  
No timber

July 20, 1911

July 18, 1911

N. 0° 02' W., bet. secs. 3 and 4

Over rolling land, through scattering shade-  
scent, chaparral and joshua, ascend15.00 Spur, 125 ft. above sec. cor., projects S. 59° E.,  
descend35.00 Ravine, 100 ft. below spur, drains S. 35° E.,  
ascend40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins.  
in the ground, for  $\frac{1}{4}$  sec. cor., with brass  
cap mkt.  $54 \frac{1}{4} | 53$   
1911and raise a mound of stone, 2 ft.  
base,  $1 \frac{1}{2}$  ft. high, W. of cor.60.00 Spur, 200 ft. above ravine, at junction with  
wide ridge, projects S. 30° E. Ridge  
bears N. 10° W. and S. 10° W.; descend  
gradually71.00 Commence abrupt descent, bears N. 60° W.  
and S. 60° E.77.50 Head of ravine, 100 ft. below spur, drains E.,  
ascend79.36 Intersect the Second Standard Parallel  
South 27.15 chs. west of S. cor. of secs. 33  
and 34, which I established July 17,  
1911

At my point of intersection

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins.  
in the ground, for closing cor. of secs.  
3 and 4, with brass cap mkt. $54 \frac{1}{4} | 53$ 

T 9 S R 67 E

1911

and raise a mound of stone, 2 ft. base,  
 $1 \frac{1}{2}$  ft. high, S. of cor.

Land, rolling