

Subdivision of T. 9 S., R. 67 E.

Chains descend
 65.10 Ravine, 125 ft. below spur, drains S. 41° E.;
 ascend
 75.00 Spur, 150 ft. above ravine, projects S. 35° E.;
 descend
 79.00 Ravine, 100 ft. below spur, drains S. 65° E.;
 ascend
 79.65 Intersect the Second Standard Parallel
 South 26.92 chs. W. of the standard cor.
 of secs. 32 and 33, which I established
 July 17, 1911
 At my point of intersection
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins.
 in the ground, for closing cor. of secs.
 4 and 5, with brass cap sunk.

55 | 54
 T9S R67E
 1911

and raise a mound of stone, 2 ft.
 base, 1 1/2 ft. high, S. of cor.
 Land, rolling.
 Soil, gravelly and rocky; 4th rate.
 No timber

July 18, 1911

July 7, 1911

From the cor. of secs. 5, 6, 31 and 32, on S.
 ldy. of T. 9 S., which I established June
 26, 1911, I run

N. 0° 03' W., bet. secs. 31 and 32

Over rolling land, through scattering shad-
 scale, chaparral and Joshua; ascend

2.50 Spur, 75 ft. above sec. cor., projects S. 45° E.;
 descend

6.80 Ravine, 50 ft. below spur, drains S. 46° E.;
 ascend

10.00 Spur, 100 ft. above ravine, projects S. 47° E.;
 descend

15.20 Ravine, 75 ft. below spur, drains S. 49° E.;
 ascend