

chains.

W. of my line.

It is a basalt stone, 8×8 ins. by 14 ins. above ground, firmly set in the ground, marked with 6 notches on the N, E, and W edges and witnessed by a mound of stone 2 ft. base $1\frac{1}{2}$ ft. high N. of cor. Since a number of the lines between corners on this bdy. are out of limits in either or both bearing and distance and some of the corners are in poor condition it will be necessary to resurvey this bdy.

Therefore I return to the cor. of Tps. 24 and 25 N, Rs. 24 and 25 E and resurvey as follows:

I destroy all traces of this corner and its accessories and re-establish it at the same point as follows:

Set an iron post 3 ft. long, 3 ins. diam. 24 ins. in the ground for cor. of Tps. 24 and 25 N, Rs. 24 and 25 E. with brass cap mkd.

T 25 N	
R 24 E	R 25 E
S 36	S 31
—	
S 1	S 6
R 24 E	R 25 E
T 24 N	
1911	

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.

Thence I run.

$50^{\circ} 5' W$ bet secs. 1 and 6

Over rough basalt mountains

- 3.10 Small ravine, course W.
- 13.00 Mountain spur, slopes W.
- 22.65 Ravine, course N. W.
- 30.00 Mountain spur, slopes W.
- 37.57 Ravine, course S. W.