

Chains. and raise a mound of stone, 2 ft. base, 1-1/2 ft. high.
W. of cor. from which the croppings of a ledge, marked
B. R. bears N. 15°00' E., 75 lks. dist.

Land, mountainous.

Soil, clay and rocks, 3rd and 4th rate.

Low sage brush, undergrowth.

No timber.

Drainage, S. and SE.

West, bet. secs. 6 and 31. ✓

Over ascending ground.

22.34 Point of cliff, 80 ft. high, bears N. 30 lks. dist.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in
the ground, for 1/4 sec. cor. with brass cap mkd:

S 31
1/4 ✓

S 6
1911

and raise a mound of stone, 2 ft. base, 1-1/2 ft. high,
N. of cor.

45.00 Top of ridge, 500 ft. above sec. cor. bears N.35°00'E.,
and S.35°00' W., gradually descend.

54.15 Enter Quaking Asp timber, bears N.30°00'E., and S.30°00'W.

64.00 Creek, 10 lks. wide, clear water, 2 ins. deep, course
N.35°00'E., ascend.

68.70 Leave Quaking Asp timber, bears N.35°00'E., and S.35°00'W.

78.69 ✓ Set an iron post, 3 ft. long, 3 ins. diam, 24 ins. in
the ground, for cor. of Tps. 47, 48 N., Rs. 33,34 E.
with brass cap mkd: