

Chains

W. bet. secs. 30 and 31.

Over level land.

27.35

Wash, course S.E.

37.50

The correct proportional distance of the length of line of original survey and plat approved Oct. 28, 1893.

Set an iron post 3 ft. long, 1 in. diam. 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. for. sec. 31 with brass cap mkd.

 $\frac{1}{4}$ 


---

S 31  
1914

dig pits 18-18-12 ins. E. and W. of post 3 ft. dist. and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high S. of cor.

40.00

Set a quartzite stone 16-7-5 ins. 11 ins. in the ground for  $\frac{1}{4}$  sec. cor. for. sec. 30, marked  $\frac{1}{4}$  on the N. face and raise a mound of stone 2 $\frac{1}{2}$  ft. base  $1\frac{1}{2}$  ft. high N. of cor.

69.24

Intersect the W. bdy. of the tp. at S 0°40'E, 2.54 chs. from the original cor. of secs. 25, 30, 31 and 36, now marked A P

At the point of intersection, set a quartzite stone 18-11-7 ins. 13 ins. in the ground for closing corner of secs.

30 and 31; marked CC on E. with 1 groove on S. and 5 grooves on N. face. Dig pits 24-18-12 ins. crosswise on each line N. and S. 3 ft. and E. of stone 7 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high E. of cor.

Land, level.

Soil; good desert loam; of good quality and depth, derived from disintegration of lime and volcanic rocks. 1st. rate. Good growth short sage brush. No timber, little grass  
General S.E. slope.

---

From the cor. of secs. 29, 30, 31 and 32

I run

N 0°46'E bet. secs. 29 and 30

Over level land

35.50

Wash, course S.E.

40.61

Midway bet. the cor. of secs. 29, 30, 31 and 32; and secs.