

Resurvey of the S Bdy. of T. 40 N., R. 18 E.

~~23~~

Chains.							
64.25	Top of rocky bluff, 160 ft. above ravine, bears N and S., abrupt descent.						
64.50	Foot of bluff, 130 ft. below top, bears N and S., descend.						
72.00	Ravine, 40 lks. wide, 60 ft. below foot of bluff, course S. 40°W., ascend, thru scattering junipers.						
80.00	Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 34 and 35, with brass cap mkd: <div style="text-align: center;"><table><tr><td>T 40 N</td><td>R 18 E</td></tr><tr><td>S 34</td><td>S 35</td></tr><tr><td colspan="2">1911</td></tr></table></div>	T 40 N	R 18 E	S 34	S 35	1911	
T 40 N	R 18 E						
S 34	S 35						
1911							
	and raise a mound of stone, 2 ft. base, 1-1/2 ft. high, N. of cor.						
	Land, mountainous.						
	Soil, rocky, 4th rate.						
	Timber, scattering juniper.						
	Low sage brush undergrowth.						
	Drainage, W.						

Survey of S. Bdy. T. 40 N., R. 18 E.

	West., on the S. Bdy. of sec. 34.
	Over ascending ground.
6.00	Ravine, 40 lks. wide, 30 ft. deep, course S. ascend.
17.75	Top of ridge, 80 ft. above ravine, bears N and S., descend.
31.50	Bottom of canyon, 2.10 chs. wide, 90 ft. below top of ridge, course S 80°W., ascend.
	Wood road in bottom of canyon, bears S 80°W.