

32.

Additional $\frac{1}{4}$ sec. cors.
 Subdivision in T.25 N., R. 18 E.

Chs.

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
 N. of cor.

$\frac{1}{4}$ sec. cor. S. of sec. 32.

On S. bdy. of township, at a point N.89°34'W.,
 5.50 chs. from the $\frac{1}{4}$ sec. cor. to sec. 5; set an iron
 post 3 ft. long, 1 in. in dia., 24 ins. in the ground
 for $\frac{1}{4}$ sec. cor. to sec. 32, with brass cap mkd:

S 32 $\frac{1}{4}$
 1912

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
 N. of cor.

Additional $\frac{1}{4}$ sec. cors. on W. Bdy. of Tp.

$\frac{1}{4}$ sec. cor. W. of sec. 32.

On W. Bdy. of township, at a point midway between the
 cor. of T.25 N., R. 18 E., and the closing
 corner of secs. 29 and 32; set a granite stone 16x10x8
 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. W. of sec.
 32, marked $\frac{1}{4}$ on the E. face, and raise a mound of
 stone 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

$\frac{1}{4}$ sec. cor. W. of sec. 29.

On W. Bdy. of township, at a point midway between
 the closing corner of secs. 29 and 32, and the closing
 corner of secs. 20 and 29; set a granite stone 14x10x7
 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 29,
 marked $\frac{1}{4}$ on E. face, and raise a mound of stone 2 ft.
 base, $1\frac{1}{2}$ ft. high, E. of cor.

$\frac{1}{4}$ sec. cor. W. of sec. 20.

On W. Bdy. of township, at a point midway between
 the closing corner of secs. 20 and 29, and the closing
 corner of secs. 17 and 20; set a basalt stone 21x12x7
 ins., 16 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 20,
 marked $\frac{1}{4}$ on E. face, and raise a mound of stone 2 ft.
 base, $1\frac{1}{2}$ ft. high, E. of cor.

$\frac{1}{4}$ sec. cor. W. of sec. 17.

On W. Bdy. of Tp. at a point N.0°25'E., 40.00 chs.
 from closing corner of secs. 17 and 20; and S.0°25'W.,
 52.33 chs. from closing corner of secs. 8 and 17; set
 a volcanic stone 17x9x6 ins., 13 ins. in the ground for
 $\frac{1}{4}$ sec. cor. to sec. 17, marked $\frac{1}{4}$ on the E. face, and
 raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, E.
 of cor.

$\frac{1}{4}$ sec. cor. W. of sec. 8.

On W. bdy. of township, at a point midway between
 the closing corner of secs. 8 and 17, and the closing
 corner of secs. 5 and 8; set a granite stone 18x11x8
 ins., 14 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 8,
 marked $\frac{1}{4}$ on E. face, and raise a mound of stone 2 ft.
 base, $1\frac{1}{2}$ ft. high, E. of cor.

$\frac{1}{4}$ sec. cor. W. of sec. 5.

On W. Bdy. of Tp. at a point N.0°25'E., 40.00 chs. from
 the closing corner of secs. 5 and 8, and S.0°25'W.,
 25.06 chs. from mile post 133; set an iron post 3 ft.