Chs.

long, 1 in in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 5, with brass cap mkd: S5-4

1912

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Additional 4 sec. cor. on N. Bdy. of Tp.

the closing corner of secs. 4 and 5, and also W. 7.50 chs. from standard $\frac{1}{4}$ sec. cor. to sec. 32; set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 5, with brass cap mkd:

> S 54 1912

and dig pits 18x18x12 ins. E. and W. of post 3 ft. dist., and raise a mound of earth 31 ft. base, 11 ft. high, S. of cor.

From this corner the house of Wm. B. Lake, a squatter bears S.74°28'E., 18.90 chs. dist.

Additional 4 sec. cors. in interior of Tp.

 $\frac{1}{4}$ sec. cor. N. of sec. 23.

On the line between secs. 14 and 23, at a point E. E. 40.00 chs. from the closing corner of secs. 22 and 23; and also E. 95 lks. from the $\frac{1}{4}$ sec. cor. S. of sec. 14; Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 23, with brass cap mkd:

S 23 1912

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

 $\frac{1}{4}$ sec. cor. N. of sec. 16.

On the line between secs. 9 and 16, at a point E. 40.00 chs. from the closing corner of secs. 16 and 17; and also E. 2.46 chs. from the \(\frac{1}{4}\) sec. cor. to sec. 9; Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for \(\frac{1}{4}\) sec. cor. to sec. 16; with brass cap mkd:

1912

and raise a mound of stone 2 ft. base, 12 ft. high, S. of cor.

 $\frac{1}{4}$ sec. cor. N. of sec. 17.

On the line between secs. 8 and 17, at a point 40.00 chs. W. of the closing corner of secs. 16 and 17; and 2.36 chs. E. of the ½ sec. cor. for sec. 8; Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for ½ sec. cor. to sec. 17, with brass cap mkd:

S 17 1912

and raise a mound of stone 2 ft. base, 12 ft. high, S. of cor.