

Resurvey of the lines bet. secs. 1 and 12, 2 and 11,  
3 and 10, 4 and 9, 5 and 8, and 6 and 7. T16N, R24E.

Chains

falling 120 chs. north of my line  
5, 6, 7 and 8. It is a basalt stone  
12 x 10 x 7 ins. Marked with 5 notches  
on the S. and E. edges, and set in  
a mound of stone.

I continue my blank line W.  
bet. secs. 6 and 7.

At 40.00 chs. I find the  $\frac{1}{4}$  sec. cor.  
falling 85 lbs. N. of my line.

It is a basalt stone 14 x 10 x 6  
ins. marked  $\frac{1}{4}$  and lying on the  
ground in a small mound of  
stone.

At 79.00 chs. I find the cor. of secs.  
1, 6, 7 and 12, falling 50 lbs. N. of  
my line.

It is a basalt stone 16 x 11 x 9 ins.  
marked with 5 notches on the S.  
and 1 notch on the N. edge and  
set in a mound of stone.

Since part of the corners are gone  
the rest in poor condition, and  
some of the lines out of limits  
in either as both alignment and  
distance it will be necessary to  
resurvey these lines

I return to the cor. of secs.  
1, 6, 7 and 12 on the E. bay, and  
resurvey as follows.

I destroy all traces of the cor. of  
secs. 1, 6, 7 and 12 and re-establish  
it at the same point as follows.

Set an iron post 3 ft. long, 3 $\frac{1}{2}$  ins.  
diam. 24 ins. in the ground for  
cor. of secs. 1, 6, 7 and 12 with  
brass cap mk'd.

