

Subdivision of T. 41 N., R. 38 E.

Chains cor.

47.50 Outcropping of granite ledge rock, bears N. and S.

54.59 Creek, 15 lks. wide, in canyon 50 ft. deep, course NW., asc.

64.00 Top of spur, bears N., desc.

76.40 Begin to asc.

86.65 Top of spur, bears N., desc.

87.04 Intersect W. bdy. of township 159 lks. N. $0^{\circ} 20'$ E. of the cor. of secs. 13 and 24; previously described. Set an iron post, 3 ft. long, 2 ins. in diam., 15 ins. in the ground to bed rock, in a mound of stone for closing cor. of secs. 18 and 19, with a brass cap, marked

T 41 N

R 37 E R 38 E

S 13	S 18
S 24	cc S 19

1913

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Land rough mountainous.

Soil clay loam and stony, 3rd. rate.

Undergrowth some scattering sage-brush.

Drains NW.

Mountainous land 87.04 chs.

N. $0^{\circ} 07'$ W. bet. secs. 17 and 18.

Asc. over rough mountainous land covered with scattering sage-brush, snow-brush, willows and cottonwoods.

29.70 Top of ridge, bears N. 60° W. and S. 60° E., desc.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 7 ins. in the ground to bed rock, in a mound of stone, for $\frac{1}{4}$ sec. cor., with a brass cap, marked

$\frac{1}{4}$ S 18	S 19 17
--------------------	---------

1913

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of