

Chs.	
	East on a random line between secs. 29 and 32.
40.00	Set a temporary $\frac{1}{4}$ sec. cor.
80.12	Intersect N. and S. line 7 lks. N. of the cor. of secs. 28, 29, 32 and 33.
	Thence I run
	N. $89^{\circ}57'W.$ on a true line between secs. 29 and 32.
	Over rolling mountainous land.
	Ascend 15 ft. on SE. slope to top of ridge.
2.50	Road, Nolan ranch to Duck Flat, bears N. $50^{\circ}E.$ and S. $50^{\circ}W.$
10.00	Ridge, bears N. $15^{\circ}E.$ and S. $15^{\circ}W.$ ; descend 235 ft. on NW. slope to ravine.
39.60	Ravine, course S. $10^{\circ}W.$ ; ascend 80 ft. on SE. slope to top of spur.
40.06	Set an iron post 3 ft. long, 1 in. in diam., 15 ins. in the ground to bedrock in a mound of stone for $\frac{1}{4}$ sec. cor., with a brass cap mkd:
	$\begin{array}{r} S\ 29 \\ \frac{1}{4} \\ \hline S\ 32 \\ 1914 \end{array}$
	and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
47.00	Spur, projects S.; descend 60 ft. on SW. slope to ravine.
57.00	Ravine, course S. $25^{\circ}E.$ ; ascend 135 ft. on SE. slope to top of ridge.
72.00	Ridge, bears N. and S.; descend 20 ft. on SW. slope to corner.
80.12	The cor. of secs. 29, 30, 31 and 32.
	The east 10 chs. and the west 8 chs. of this mile consists of rolling land. The remainder is mountainous. The soil is all very rocky and unfit for cultivation. There is a sparse growth of sagebrush and a little bunchgrass. No timber.
	August 1, 1914.
	August 5: At 9 h 10 m A.M., l.m.t., I set off $41^{\circ}13.5'$ on the lat. arc and $17^{\circ}6'N.$ on the decl. arc, and determine a meridian with the solar at the cor. of secs. 29, 30, 31 and 32, heretofore described.
	Thence I run
	West on a true line between secs. 30 and 31.
	Over rolling mountainous land.
	Descend 20 ft. on SW. slope to head of draw.
7.50	Head of draw, course S. $20^{\circ}E.$ ; ascend 115 ft. on E. slope to top of ridge.
27.50	Ridge, bears N. and S.; descend 520 ft. into Wall Canyon, beginning on SW. slope.
40.00	Spur, projects SW.; slope changes to NW.
	Set an iron post 3 ft. long, 1 in. in diam., 9 ins. in the ground to bedrock in a mound of stone for $\frac{1}{4}$ sec. cor., with a brass cap mkd:
	$\begin{array}{r} S\ 30 \\ \frac{1}{4} \\ \hline S\ 31 \\ 1914 \end{array}$
	and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
62.90	Wall Creek, flowing, clear water, 12 lks. wide, 6 ins. deep, course S. $15^{\circ}W.$ ; ascend 90 ft. on SE. slope to top of spur.
66.60	Spur, projects SE.; thence along south slope.
69.30	Brook, slightly flowing S. $80^{\circ}E.$ ; ascend 375 ft. on NE. slope to Closing Corner.
95.27	Intersect the W. Bdy. of the township at a point S. $0^{\circ}12'E.$ 10.69 chs., from the cor. of secs. 25 and 36, heretofore described, and at point of intersection set an iron