

4. Resurvey of S. bdy. of T. 23 N., R. 19 E.

Chains

cap marked

S36 $\frac{1}{4}$

1914

dig pits, 18x18x12ins. N. and S. of cor., 3 ft. dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

79.44

Intersect the corner of T. 23 N., Rs. 19 and 20 E. heretofore described. This corner is 15 ft. above wash. Land, rolling. Soil, a deep sandy clay loam, with gravelly subsoil. Vegetation, sagebrush. No grazing No timber. Drainage to the N.E.

Nov. 18, 1914.

RESURVEY OF SOUTH BDY. OF T. 23 N., R. 19 EAST

Dec. 1, 1914: At 8h 0m a.m., l.m.t., I set off $39^{\circ}49'$ N. on the lat. arc, $21^{\circ}39'S$ on the decl. arc and determine a meridian at the corner of T. 22 N., Rs. 19 and 20 E.

Thence I run

S. $89^{\circ}49'W$. on a true line along the N. bdy. of sec. 1. Ascend, over rolling ground.

4.14

Intersect the cor. of T. 23 N., Rs. 19 and 20 E., which is a granite rock heretofore described.

40.39

Proportional distance.

Set an iron post, 3 ft. long, 1 in. in dia., 24 ins. in the ground for $\frac{1}{4}$ cor. of sec. 1, with brass cap marked

 $\frac{1}{4}$

S1

1914

dig pits, 18x18x12ins. E. and W. of cor., 3 ft. dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high S. of cor.

43.35

Set an iron post, 3 ft. long, 1 in. in dia., 24 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 36, with brass cap marked

S36

 $\frac{1}{4}$

1914

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

48.30

This cor. is 65 ft. above Tp. corner.

83.35

Wash 20 lks. wide, 4 ft. deep, course N. E.

A point, (80.00 chs. minus the easting of the E. bdy.)

79.21 chs. from the S. E. cor. of T. 23 N., R. 19 E.

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, for cor. of secs. 35 and 36, with brass cap marked

T23N | R19E

S35 | S36

T22N

1914

and build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

This cor. is 150 ft. above $\frac{1}{4}$ sec. cor.