

## SUBDIVISION OF T.16 N., R.22 E.

## Chains

South bet. secs. 13 and 14; descend very steep.

8.50 Set a basalt rock, 20x12x4 ins. 12 ins. in the ground, the for witness cor. to cor. of secs. 11, 12, 13 and 14, mkd. with 4 notches on the S., and 1 notch on the E. faces, and W C on the N. face; and raise a mound of stone 2 ft. base, 1½ ft. high W. of cor.

*Iron post impracticable*

~~and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.~~

From the witness cor. above described I run East on offset line; ascend 40° slope.

11.10 Top of steep ascent; thence, ascend gradually over frequent unimportant ridges and gulches.

35.00 Point from which I run

North to true line; ascend.

8.50 Point on true line 35.00 chs. E. of cor. of secs. 11, 12, 13 and 14. Thence, I run

East on true line bet. secs. 12 and 13; ascend gently.

40.00 (or 5 chs. E. of point on true line) Set a basalt stone, 18x14x5 ins., 12 ins. in the ground, for ¼ sec. cor., mkd. ¼ on the N. face; and raise a mound of stone 2 ft. base, 1½ ft. high, N. of cor. Iron post impracticable.

47.50 Descend into draw, course S.

60.00 Bottom of draw near head, course S.; ascend.

76.22 Intersect E. bdy. of the Tp., 1.64 chs. N0°10'E of the closing cor. of secs. 7 and 18, heretofore described. At the point of intersection, I establish the closing cor. of secs. 12 and 13 as follows.

At the exact corner point I chisel a cross on a rock in place, showing 6x3x2 ft. above ground, mkd. with 2 grooves on the N. and 4 grooves on the S. sides, with R 22 E on the W. and R 23 E on the E. sides and T 16 N C C, on the top thereof, and raise a mound of stone 2 ft. base, 1½ ft. high W. of cor. Iron post impracticable.