17.

Subdivision of T.22 N., R. 24 E. Chains Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for the cor. of secs. 21, 22, 27 and 28, 80.00 with brass cap mkd: T22N R24E S21 S22 S28 S27 1915 and raise a mound of stone 2 ft. base, la ft. high, W. of cor. Land, mountainous. Soil, fine clay loam, rocky and gravelly; two to ten inches deep. Surface covered with loose lava boulders. Vegetation, sagebrush, greasewood and scattering growth of bunchgrass. Some grazing. No timber. Drainage 40.00 chs. to the east and 40 chs. to the west. From the Cor. of secs. 21, 22, 27 and 28, I run S.0°07'W. on a true line between secs. 27 and 28. Over mountainous land, descend.
Bottom of draw, 10 ft. below sec. cor., course N.70°E.; 5.00 ascend. Point of spur, 180 ft. above bottom of draw, projects 24.85 W.; descend. Draw, 10 ft. below spur, course N.70°W.; ascend. Set an iron post 3 ft. long, 1 in. in dia., 18 ins. in the ground to solid rock, and in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd: 29.85 40.00 S28 S27 1915 and raise a mound of stone 2 ft. base, $l^{\frac{1}{2}}$ ft. high, W. of cor. Top of ridge, 480 ft. above the bottom of a draw, bears N.55°E. and S.70°W.; descend 380 ft. to the closing corner. Intersect the Pyramid Lake Indian Reservation boundary 9.66 chs. S.21°50'E. of the 13th mile post, which is an 62.70 iron post 1 inch in dia., marked and witnessed as described by the Surveyor General. At the point of intersection I build a corner as follows:

Set an iron post 3 ft. long, 2 in. in dia., 24 ins. in the ground for closing corner of secs. 27 and 28, with brass cap mkd: TZZN R24E P \S28 S27 and raise a mound of stone 2 ft. base, l_{2}^{1} ft. high, N. of cor. Land mountainous. Soil, clay loam, rocky and gravelly, 10 ins. deep, gravelly and rocky subsoil. Surface covered with Vegetation, sagebrush, greasewood, scattering lava rocks. growth of bunchgrass. No timber. Drainage 52.40 chs. N.E.; 10.60 chs. south.

> From the cor. of secs. 21, 22, 27 and 28, I run West on a true line between secs. 21 and 28. Over heavy rolling land, ascend.

Top of ridge, 25 ft. above section corner, bears NE. and SW.; descend 90 ft. to the closing corner. 11.00