

22.

Subdivision of T.22 N., R. 24 E.

Chains

and raise a mound of stone 2 ft. base, 1½ ft. high,  
W. of cor.  
Descend gradual slope.  
54.80 Road, bears S.30°W. and N.30°E.  
59.13 Dry wash, 10 lks. wide, 2 ft. deep, 80 ft. below ¼ sec.cor.  
course S.70°W.; ascend 40 ft. to the sec. cor.  
80.01 The cor. of secs. 3, 4, 9 and 10.  
Land, rolling and hilly.  
Soil, rocky clay loam with rocky subsoil.  
Vegetation, sagebrush, sheep brush, and greasewood.  
No grazing.  
No timber. Drainage southerly.

May 8, 1915.

May 8, 1915: For solar on this date see survey of line  
between secs. 15 and 16.  
From the cor. of secs. 9, 10, 15 and 16, I run  
West on a true line between secs. 9 and 16.  
Over rolling land, descend.  
23.50 Ravine, 140 ft. below section corner, course NW.; asc.  
36.65 Top of ridge, 80 ft. above ravine, bears N. and S.,  
desc.  
40.00 Set an iron post 3 ft. long, 1 in. in dia., 18 ins.  
in the ground to solid rock and in a mound of stone  
for ¼ sec. cor., with brass cap mkd:

S 9  
¼  
S 16  
1915

and raise a mound of stone 2 ft. base, 1½ ft. high,  
N. of cor.  
57.54 Dry wash, 20 lks. wide, 4 ft. deep, 95 ft. below top of  
ridge, course NW.; ascend 200 ft. to the sec. cor.  
80.00 Set an iron post 3 ft. long, 2 ins. in dia., 10 ins.  
in the ground to solid rock and in a mound of stone  
for the cor. of secs. 8, 9, 16 and 17, with brass  
cap mkd:

T22N | R24E  
S8 | S9  
S17 | S16  
1915

and raise a mound of stone 2 ft. base, 1½ ft. high,  
W. of cor.  
Land rolling.  
Soil, sandy clay loam with gravelly and rocky subsoil.  
Vegetation, scanty sagebrush, sheep brush, greasewood.  
No grazing.  
No timber. Drainage northwest.

From the cor. of secs. 8, 9, 16 and 17, I run  
West on a true line between secs. 8 and 17.  
Gradually ascend over rolling land.  
6.96 Top of ridge, 45 ft. above section corner, bears N. and  
S.; descend 10 ft. to the closing corner.  
9.87 Intersect the Pyramid Lake Indian Reservation Boundary  
5.72 chs. S.21° 52'E. of the Station No.4, which is an  
iron post 3 ins. in dia., firmly set in the ground,  
marked and witnessed as described by the Surveyor General.  
At the point of intersection I build a corner as follows:  
Set an iron post 3 ft. long, 2 ins. in dia., 12 ins.  
in the ground to solid rock and in a mound of stone for  
the closing corner of secs. 8 and 17, with brass cap mkd:

T22N R24E  
P S8  
L C  
I C  
R S17  
1915

and raise a mound of stone 2 ft. base, 1½ ft. high,  
E. of cor.