Retracement of E. Bdy. of T. 21 N., R. 25 E. Chains From the $\frac{1}{4}$ sec. cor., I continue North. Intersect the cor. of secs. 1, 6, 7 and 12, which is a 80.00 lava stone 8x10x12 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. Therefore the true course and distance is North, 39.89 chs. North, retracing between secs. 1 and 6. Fall 2 lks. W. of the $\frac{1}{4}$ sec. cor., which is a lava stone 10x10x12 ins. above ground, firmly set, marked and 40.12 witnessed as described by the Surveyor General. Therefore the true course and distance is N.0°02'E., 40.12 chs. From my transit station 2 lks. W. of the $\frac{1}{4}$ sec. cor., I continue North Fall 1 lk. W. of the closing cor. on the N. bdy. which 73.84 is a lava stone 10x10x12 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General; the closing corner is 2.83 chs. distant East of the cor. of Tp. 22 N., Rs. 25 and 26 E., heretofore described. Therefore the true course and distance of this half mile is N.O°l'W., 33.72 chs. RESURVEY OF FOURTH STD. PAR. N., thru R.25 E. For solar see line between secs. 31 and 36 on May 13: the E. Bdy. From the Std. Cor. of T. 21 N., Rs. 25 and 26 E., heretofore described, I run

West, resurveying along the S. Bdy. of sec. 36. Over level flat or old lake bed, with scattering low

11.61 40.06

80.06

sand dunes.

Fall 2 lks. N. of the Closing Corner.

Fall 11 lks. N. of the Standard 4 sec. cor., which is a scoria stone 8x10x12 ins. above ground, firmly set, and properly marked. I reestablish this corner, by setting alongside of the stone an iron post 3 ft. long, l in. in dia., 26 ins. in the ground, with brass cap mkd:

S 364 1915

and dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth 31 ft. base, 11 ft. high, N. of cor.

Therefore the true course and distance of this half mile is S.89°51'W., 40.06 chs.

From my transit station 11 1ks. N. of the Std. 4 sec. cor.,

I continue West. 58.16

Road, bears NW. and SE., from Leete to Hazen.
Fall 10 lks. N. of the Standard Cor. of secs. 35 and 36, which is a lava stone 8x8x14 ins., above ground, firmly set and properly marked. I reestablish this corner by setting alongside of the stone an iron post 3 ft. long, 3 ins. in dia., 24 ins. in the ground, with brass cap mkd: T21N R25E

\$35 | \$36 \$ | C 1915

and dig pits 24x18x12 ins. crosswise on each line E. and W. 3 ft. and N. of post 7 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, N. of cor. Therefore the true course and distance of this half mile is N.89°59'W., 40.00 chs. Land, level lake bed: Soil, alkali and some sandy on dunes. Undergrowth, scattering greasewood: No timber.