

6.

Subdivision of T.21 N., R. 25 E.

Chains

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.
72.20 Draw, course SE. Ascend N.E. slope 70 ft. to
79.80 200 ft. below $\frac{1}{4}$ sec. cor.
The cor. of secs. 1, 2, 11 and 12.
Land, rolling with a general W.W. and S. slope;
S.E. exposure and drainage.
Soil, light loose sandy and gravelly, mixed with
rocks, 3rd rate.
Undergrowth, scant greasewood.
No timber.

May 24, 1915.

For solar observation see line between secs. 14 and 15.
May 25: Knowing that a closing corner will be necessary
on the North Bdy., I run
N.0°4'W. on a true line between secs. 1 and 2.
Over rolling land, general slope to the E.
3.60 Draw, course S.75°E.; ascend 110 ft. to
12.87 Low spur, slopes E.; descend 45 ft. to
18.77 Draw, course SE.
40.00 114 ft. above section corner.
Set an iron post 3 ft. long, 1 in. in dia., 26 ins.
in the ground for the $\frac{1}{4}$ sec. cor., with brass cap
mkd:

$\frac{1}{4}$
S2 | S1
1915

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.
42.60 Draw, course S.75°E., ascend 80 ft. to
50.00 Ridge spur, slopes E., and bears about W.
54.85 Draw, course S.70°E., ascend 60 ft. to
59.75 Spur, slopes E.; descend.
73.67 Intersect the N. bdy. of the township, 2.84 chs. N.89°
59'E. of the cor. of secs. 1, 2, 35 and 36, heretofore
described. At the point of intersection I

Set an iron post 3 ft. long, 2 ins. in dia., 18 ins.
in the ground to solid rock and in a mound of stone
for the closing corner of secs. 1 and 2, with brass
cap mkd.

$\frac{1}{2}$ N
T21N | R25E
S35 | S36
C | C
S2 | S1
T21N
1915

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
S. of cor. I destroy all marks on the old corner
pertaining to sections 1 and 2.
Land, rolling, general drainage to the east.
Soil, light sandy and gravelly loams, mixed with rocks.
8 to 10 ins. deep, on rocky subsoil; 3rd rate.
Undergrowth, short scattering greasewood and sheep
brush.
No timber.

May 25, 1915.
Andrew Nelson
U.S. Transitman.

May 17: For solar observation see line between secs.
35 and 36.
From the standard corner of secs. 34 and 35 on the S.
Bdy. of the township, heretofore described, I run
N.0°4'W. on a true line between secs. 34 and 35.
Over sandy land, through greasewood.
1.00 Leave sandy ground, enter old lake bed with alkali soil,
bears N.70°W. and S.70°E.