

SUBDIVISION OF T.24 N., R.26 E.

Chains	West on a true line bet. secs. 30 and 31.
	Descend gradually over heavily rolling land; drainage N.E.
22.40	Dry wash, 10 lks. wide, course, N.
31.50	Main dry wash, 50 lks. wide, course, N.E.
35.00	Beginning of ascent, gently at first gradually becoming steeper.
40.00	Set an iron post, 3 ft. long. 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.;
	<div>S 30 $\frac{1}{4}$ S 31 1911</div>
	and dig pits, 18x18x12 ins. E. and W. of the post, 3 ft. dist., and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
60.00	Top of high ridge, bears N: and S.; descend.
67.50	Bottom of gulch and dry wash, 50 lks. wide, course S.
79.40	Interscet the W. bdy. of the tp. 13.42 chs. S. of the cor. of secs. 25,30,31 and 36, which is an iron post, 1. ft. above ground, 3 ins. diam., with mound of stone W. of cor. (I change the markings on this post to indicate a corner common to the 2 secs. 25 and 36. At the point of intersection
	I set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 30 and 31, with brass cap mkd.;
	<div>T 24 N S 25 R 25 E S 36 CC S 30 S 31 T 24 N 1911</div>
	and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.
	From the closing corner, above described I run
	South on west bdy. of sec. 31
26.58	An iron post 1 ft. above ground, 1 in. diam., with mound of stone on the west for $\frac{1}{4}$ sec. cor. marked to refer to secs. 31 and 36, which I change to refer to sec. 36 only