## SUBDIVISION OF T.24 N., R.26 E.

Chains
West on a true line bet. secs. 7 and 18.
Ascend gradually over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., with brass cap mkd.;

and dig pits, 18x18x12 ins., E. and W. of the post, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

47.10 Dry wash, 40 lks. wide, course N.; ascend steep.

68.50 Top of high ridge, bears N.W. and S.E.; descend.

79.39 Intersect the W. bdy. of the tp. 13.56 chs. S. of the cor. of secs. 7,12,13 and 18, which is an iron post, 1 ft. above ground, 3 ins. diam., with a mound of stone W. of cor. I change the markings on this post to indicate a corner common to the 2 secs. 12 and 13. At the point of intersection

I set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing corner of secs. 7 and 18, with brass cap mkd.;

and raise a mound of stone, 2 ft. base,  $l\frac{1}{2}$  ft. high, E. of cor.

From the closing corner above described, I run South on the west bdy. of sec. 18.

26.44 An iron post, l. ft. above ground, l in. diam., with a mound ofstone on the W., for 4 sec. cor, marked to refer to secs. 13 and 18, which I change to refer to sec. 13 only.

39.975 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor. of sec. 18, with brass cap mkd.;