

Re-survey of the 5th. Standard Parallel
North, through R26E.

Chains

S 89° 50' E, south of sec. 35

Descending over rolling granite hills.

4.60 Road bears N. and S.

24.10 Ravine, course N.E.

40.04 ✓ Set an iron post 3 ft. long, 1 in.
diam. 24 ins. in the ground for
standard $\frac{1}{4}$ sec. cor. with brass
cap m'kd.

S 35
 $\frac{1}{4}$ ✓

1911

and raise a mound of stone 2 ft.
base, $1\frac{1}{2}$ ft. high N. of cor.
thence across level land.

80.08 ✓ Set an iron post, 3 ft. long, 3 ins.
diam. 24 ins. in the ground for
standard corner of secs. 35 and 36
with brass cap m'kd.

T 26 N R 26 E
S 35 | S 36
—|— ✓

1911

dig pits 24 x 18 x 12 ins. crosswise on each
line, E. and W., 3 ft. and N. of post,
7 ft. dist.; and raise a mound of earth,
4 ft. base, 2 ft. high, N. of cor.

Land, rolling and level.

Soil, sandy and stony; and good, rich
loam. 3rd and 1st. rate.

W. 40.04 chs. is unfit for cultivation.

E. 40.04 chs. is good land, derived from
disintegration of granite rocks.

Fair growth sagebrush, little grass
no timber, slopes N.E.

S 89° 50' E, south of sec. 36.

Over level land

28.00 Low ridge, bears N.E. and S.W.

40.04 Set an iron post, 3 ft. long, 1 in.