

Subdivisions of T. 23 N., R. 27 E.

Chains.

38.00 Wash, course SW.
40.00 Set an iron post 3 ft. long, 1 in. diam. 26 ins. in ground for 1/4 sec. cor. marked on brass cap:

S 30
1/4
S 31
1911

dig pits 18x18x12ins. E. and W. of post 3 ft. dist. and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high N. of cor.

75.35 The cor. of secs. 25, 30, 31 and 36, on the W. Bdy.

Land heavily rolling.
Soil, a heavy sand mixed with gravel.
Scattering desert brush.

Sept. 13, 1911

Sept. 15, 1911. At 8 h 00 m A.M., l.m.t., I set off 39°49' N. on the lat. arc, 3°19 1/2' N. on the decl. arc, and determine a meridian with the solar at the cor. of secs. 25, 26, 35 and 36.

Thence I run N.0°01'W. bet. secs. 25 and 26.

Over heavily rolling land.

35.00 Butte 100 ft. high bears W. 5 chs.

40.00 Set an iron post 3 ft. long, 1 in. diam. 26 ins. in the ground for 1/4 sec. cor. marked on brass cap:

S 26 1/4 | S 25
1911

and raise a mound of stone 2 ft. base, 1 1/2 ft. high W. of cor.

51.00 Wash 40 lks. wide, course NE.

75.00 Foot of bluff, asc.

76.00 Top of bluff, 40 ft. high, bears N.15°E. and S.15°W.

80.00 Set an iron post 3 ft. long, 2ins. diam. 24ins. in ground for cor. of secs. 23, 24, 25 and 26 marked on brass cap:

T 23 N R 27 E
S 23 | S 24
S 26 | S 25
1911

and raise a mound of stone 2 ft. high 3 ft. base, W. of cor. This cor. at foot of bluff.

Land, heavily rolling.

Soil, rocky, scattering desert brush.

East on a true line bet. secs. 24 and 25.

Desc. over broken ground. Runs out at 2 chs. N. Desc.

1.50 Edge of low bluff, bears N.15°E. and S.15°W.

2.00 Foot of bluff, thence over rolling land, desc.

7.37 Road, bears NW. and SE.

27.00 Wash, 50 lks. wide, course N. 30°E.

40.00 Set an iron post 3 ft. long, 1 in. diam. 26 ins. in ground for 1/4 sec. cor. marked on brass cap:

S 24
1/4
S 25
1911

and raise a mound of stone 2 ft. base, 1 1/2 ft. high N. of cor.

80.02 Intersect E. Bdy. Tp. 9.01 chs. S.0°1'W. of cor. of secs. 19 and 30.

Set an iron post 3 ft. long, 2ins. diam. 24ins. in ground for closing cor. of secs. 24 and 25, marked on brass cap:

T 23 N
S 24 | S 19
S 30
cc R 28 E
S 25 |
R 27 E
1911