

SUBDIVISION OF T.24 N., R.27 E.

- Chains
45.25 ✓ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.;
- $$\begin{array}{r} S\ 1 \\ \frac{1}{4} \\ \hline S\ 12 \\ 1911 \end{array}$$
- and dig pits, 18x18x12 ins., E. and W. of the post, 3 ft. dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
- 53.40 Wide dry wash, 1 ch. wide, course, N.; ascend E. slope of main ridge.
- 64.30 Top of main ridge, bears N.E. and S. W.; descend.
- 85.25 ✓ The cor. of secs. 1,2,11 and 12.
Land mountainous.
Soil, sand mixed with gravel in bottom land and rocky on the tops of ridges; 3rd. and 4th. rate.
No timber; desert brush.
Mountainous land, 80.00 chs.
-
- N. on sectional guide meridian, bet. secs. 1 and 2, on a true line.
Descend gradually over heavily rolling land.
- 40.00 ✓ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.;
- $$\begin{array}{r} S\ 2\ \frac{1}{4} \quad S\ 1 \\ 1911 \end{array}$$
- and dig pits, 18x18x12 ins., N. and S. of the post, 3 ft. dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 85.00 ✓ Intersect the N. bdy. of the Tp., 6.22 chs. S89°20'W from the cor. of secs. 35 and 36, hereto fore described. At the point of intersection I
set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing corner of secs. 1 and 2, with brass cap mkd.;