

RESURVEY OF THE
5th. STANDARD PARALLEL NORTH, THROUGH R.27 E.

Chains

stake in E. pit. I reestablish this corner at the same point as follows:-

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for Standard sec. cor. of secs. 35 and 36, with brass cap mkd.;

T 25 N | R 27 E
SC S 35 | S 36 ✓

1911;

dig pits, 24x18x12 ins., crosswise on each line, E. and W. 3 ft., and N. of the post 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, N. of cor.; thence, I run (bearing of last $\frac{1}{2}$ mile is S 89°42'E) ✓

S 89°42'E on the S. bdy. of sec. 36, along the continuation of the same line.

40.00 The Standard $\frac{1}{4}$ sec. cor. bears N. 2 lks.; a mound of earth over corner, and pits, with marked stake in E. pit. I reestablish this corner at the same point as follows:-

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for Standard $\frac{1}{4}$ sec. cor. of sec. 36, with brass cap mkd.;

S C $\frac{1}{4}$ S 36

1911;

and dig pits, 18x18x12 ins., E. and W. of the post, 3 ft. dist., and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. (bearing of last $\frac{1}{2}$ mile is S 89°42'E)

58.97 Dry wash, 75 lks. wide, course, N. (Sage Hen wash.)

79.98 The Standard Tp. corner of Tp. 26 N., Rs. 27 and 28 E., bears N. 2 lks., which is a quartzite stone, 14x12x10 ins. above ground, firmly planted, with mound of stone on the N., mkd. S C and 6 grooves on the N. face and 6 grooves on the E. and W. faces. (bearing of last $\frac{1}{2}$ mile is S 89°42'E) October 18, 1911.

GENERAL DESCRIPTION.

This line passes over gently rolling land for its entire length. The soil is mainly a loose sand mixed with gravel. There is no timber or grass along this line,