

18.


Subdivision of T. 25 N., R. 27 E.

Chains

79.92 The cor. of secs. 2, 3, 10 and 11.  
Land gently rolling.  
Soil sandy, 3rd rate.  
No timber; desert brush.


N. 0° 05' W. on a true line bet. secs. 2 and 3.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.;



dig pits, 18x18x12 ins., N. and S. of the post, 3 ft. dist; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

83.24 Intersect the N. bdy. of the Tp. which is the 5th Standard Parallel, 7.42 chs., S. 89° 42' E. of the Standard corner, of secs. 34 and 35, heretofore described. At the point of intersection, I Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing corner of secs. 2 and 3, with brass cap mkd.;



dig pits, 24x18x12 ins., crosswise on each line, E. and W. 3 ft., and S. of the post 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, S. of cor.

Land rolling.  
Soil sandy; 3rd rate.  
No timber; desert brush.

October 19, 1911.