

SUBDIVISION OF T. 36 N., R. 29 E.

Chains.	
45.00	Top of spur, bears N. and S.; thence, along N. slope.
52.00	Head of draw, course N.
60.00	Top of spur, bears N. and S.; descend steep.
72.84	Intersect the W. bdy. 75 lks. N. of the old cor. of secs. 1, 6, 7 and 12, heretofore described. At the point of intersection I
	Set a sandstone, 18x12x10 ins., 12 ins. in the ground, for closing cor. of secs. 6 and 7, marked CC on the E.; with 5 grooves on the S. and 1 groove on the N. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.
	From the closing cor. of secs. 6 and 7 above described, I run
	Southward , on the W. bdy. of sec. 7.
0.75	Old cor.
39.98	Set a basalt rock, 18x12x12 ins., 12 ins. in the ground, for ¼ sec. cor. of sec 7, marked ¼ on E. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.
	From the same closing cor. of secs. 6 and 7, I run
	Northward , on the W. bdy. of sec. 6.
39.21	Old ¼ sec. cor.
40.00	Set a granite stone, 27x8x4 ins., 20 ins. in the ground, for ¼ sec. cor. of sec. 6; marked ¼ on the E. face; dig pits, 18x18x12 ins., N. and S. of stone, 3 ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, E. of cor.
	Land mountainous.
	Soil, rock strewn; 4th. rate.
	No timber; desert brush.
	Mountainous land, 80.00 chs.

Knowing that a line from the cor. of secs. 5, 6, 7 and 8 running N.0°04'W., will intersect the N. bdy. of the Tp. at a distance from the old cor. on the said N.