


Resurvey of the N. bdy. of T. 26 N., R. 30 E.

Chains Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

80.00 Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground for cor. of secs. 1, 2, 35 and 36, with a brass cap, marked

T 27 N R 30 E



1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Surface level.

Soil sandy and gravelly, 3rd. rate.

Undergrowth scattering sagebrush.

Drains NE.

East on a true line bet. secs. 1 and 36.

Over level land covered with scattering sagebrush.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked

$\frac{1}{4}$ S 36

S 1

1912


Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

47.20 Wagon road, bears NW. and SE.

79.42 Intersect the E. bdy. of the township 3.82 chs. N. of the cor. of Tps 26 and 27 N., Rs. 30 and 31 E.

Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground for closing cor. of Tps. 26 and 27 N., R. 30 E., with a brass cap, marked

T 27 N



1912