

*Three*

Resurvey of the Fifth Standard Parallel N., R. 30 E.

Chains

June 24, 1912.

Beginning at the Standard cor. of T. 26 N., Rs. 29 and 30 E., at 9 h., a. m., 1. m. t., I set off  $23^{\circ} 26'$  N. on the decl. arc and  $40^{\circ} 4'$  N. on the lat. arc and determine a meridian with the solar: thence I run

East on a random line along the S. bdy. of sec. 31. and

Over level land covered with scattering sagebrush.

6.02 Intersect trace of cor. of Tps. 25 N., Rs. 29 and 30 E.  
39.95 Intersect a point 5 lks. N. of the old  $\frac{1}{4}$  standard sec.

cor., which is a granite stone, 4 X 12 X 8 ins.

above ground, marked and witnessed as described by

the Surveyor General: I destroy all trace of the

old cor. and rebuild at the same point as follows:

Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{5}{4}$  sec. cor. with a brass cap, marked

$$\begin{array}{c} \frac{1}{4} S 31 \\ \hline S 6 \\ 1912 \end{array}$$

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. Course of this half mile S.  $89^{\circ} 56'$  E.

Beginning at the  $\frac{1}{4}$  cor. above described I continue to retrace east and at

80.04 Intersect a point 10 lks. S. of the Standard cor. for secs. 31 and 32 which is a lime stone, 6 X 6 X 8 ins. above ground, marked and witnessed as described by the Surveyor General. I destroy all trace of the old cor. and rebuild at the same point, as follows:  
Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground for new standard cor. of secs. 31 and 32, with a brass cap, marked

$$\begin{array}{ccc} T 26 N & & R 30 E \\ & & | \\ & S 31 & S 32 \\ & \hline & S 6 & \\ & S 6 & S 5 \\ T 24 N & & R 30 E \\ & & | \\ & & 1912 \end{array}$$

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. Course of last half mile N.  $89^{\circ} 51'$  E.