Chains

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for ¼ sec. cor., with a brass cap, marked

¼ S 33 | S 34

1912

Dig pits 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist. and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

44.20 Wagon road, bears NE. and SW.

83.15 Intersect Fifth Standard Parallel N. 0.88 chs. N. 89° 27' E. of the re-established standard cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 33 and 34, with a brass cap, marked

T 26 N R 30 E

S 33 | S 34

cc

1912

Dig pits 18 X 24 X 12 ins., crosswise of the line, E. and W. of post 3 ft. dist., and N. 7 ft., and raise a mound of earth, 4 ft. base, 2 ft. high, N. of cor.

Surface level.

Soil sandy, 3rd. rate.

Undergrowth scattering sagebrush.

Drains S.

~~I destroy the markings on the post set from standard cor. of secs. 33 and 34, at N. side~~

Beginning at the closing cor. of secs. 33 and 34 on the Fifth Standard Parallel N., I run S 89° 27' W. on a blank line along the S. bdy. of sec. 33.

0.88 Cor. of secs. 3 and 4. Thence N 89° 42' W.

40.19 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for ¼ sec. cor., with a brass cap, marked

¼ S 33

1912

Dig pits 18 X 18 X 12 ins. E. and W. of post, 3 ft. dist.