


Subdivision of T. 27 N., R. 30 E.

Chains Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of  
 45.00 cor.  
 Asc.  
 53.80 Top of hill, bears N. and S.  
 55.80 Desc.  
 63.30 Gully and dry wash, 16 lks. wide, course NE., asc.  
 75.60 Top of ridge, bears E. and W.  
 79.64 Intersect W. bdy. of the township 1.64 chs. S.  $0^{\circ} 35'$  E.  
 of the cor. of secs. 7, 12, 13 and 18.  
 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins.  
 in the ground for closing cor. of secs. 7 and 18,  
 with a brass cap, marked

T 27 N



1912

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of  
 cor.


Surface rolling.

Soil gravelly and stony, 4th. rate.

No undergrowth.

Drains NE.

North<sup>o</sup> on a sectional guide meridian bet. secs. 7 and 8.  
 Over level land covered with scattering sage brush.  
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor., with a brass cap, marked



1912

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of  
 cor.

66.50 Dry wash, 30 lks. wide, course S.  $60^{\circ}$  E.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 18 ins.  
 in the ground to bedrock, in a mound of stone for  
 cor. of secs. 5, 6, 7 and 8, with a brass cap, marked