


Subdivision of T. 27 N., R. 30 E.

Chains Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 66.10 Dry wash, 20 lks. wide, course S.  $35^{\circ}$ E., asc.  
 80.00 Top of ridge, bears N.  $15^{\circ}$ E. and S.  $15^{\circ}$ W.  
 81.60 Intersect N. bdy. of township 3.25 chs. W. of the cor. of secs. 34 and 35.  
 Set an iron post 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, in a mound of stone for closing cor. of secs. 2 and 3, with a brass cap, marked



1912

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.

Surface rolling.

Soil gravelly and stony, 4th. rate.

No undergrowth.

Drains SE.

July 17, 1912.

July 17, 1912.

At 8 h., a. m., 1. m. t., at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the township, I set off  $21^{\circ} 13'$  N. on the decl. arc and  $40^{\circ} 10'$  N. on the lat. arc and determine a meridian with the solar; thence I run

N.  $0^{\circ} 3'$  E. bet. secs. 35 and 36.

Over level land.

9.45 Wagon road, bears N.  $80^{\circ}$ E. and S.  $80^{\circ}$ W.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor., with a brass cap, marked

