

Subdivision of T. 27 N., R. 30 E.

Chains

- 26.50 Top of ridge, bears NW. and SE., desc.
 34.80 Foot of ridge, enter level land, bears N. and S.
 39.99 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked

$$\frac{1}{4} \text{ S } 14$$

S 23

1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 79.98 Cor. of secs. 13, 14, 23 and 24.
 Surface level and rolling.
 Soil sandy and gravelly, 3rd. rate.
 No undergrowth.
 Drains SE.

East bet. secs. 13 and 24.

- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked

$$\frac{1}{4} \text{ S } 13$$

S 24

1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 77.87 Intersect E. bdy. of township 2.38 chs. N. $0^{\circ} 13'$ E. of the cor. of secs. 18 and 19.
 Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 13 and 24, with a brass cap, marked

T 27 N.
 R 30 E R 31 E
 S 13 S 18
 S 24 S 19
 cc
 1912

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.