

Subdivision of T. 27 N., R. 30 E.

Chains East bet. secs. 1 and 12.
Over rolling land.

20.00 Dry wash, 15 lks. wide, course SE., asc.

32.20 Top of low ridge, bears NW. and SE., desc. gradually.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked

$$\frac{1}{4} S 1$$

$$S 12$$

$$1912$$

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

77.01 Intersect E. bdy. of township 1.26 chs. N. $0^{\circ} 29'$ W. of the cor of secs. 6 and 7.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 1 and 12, with a brass cap, marked

$$T 27 N$$

$$R 30 E \quad R 31 E$$

$$S 1 \quad S 6$$

$$S 12 \quad S 7$$

$$1912$$

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Surface rolling.

Soil sandy and gravelly, 3rd. rate.

No undergrowth.

Drains SE.

N. $0^{\circ} 3'$ E. bet. secs. 1 and 2.

Asc. over rolling land.

1.20 Top of ridge, bears N. 70° E. and S. 70° W., desc.

14.70 Gully, 15 lks. wide, course SE., asc.

28.00 Top of ridge, bears NW. and SE., desc.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, in a mound of stone for $\frac{1}{4}$ sec. cor., with a brass cap, marked