

Subdivision of T. 30 N., R. 30 E.

chains.
 57.30 2 ft. base 1 1/2 ft. high, N. of cor.
 79.82 Wash 3 lks. wide, course S. 80° E.
 The cor. of secs. 1, 2, 11 and 12 on top
 of ridge bearing N. 10° E. and S. 10° W.
 Land, rolling
 Soil, sandy and rocky; 1st and 2nd
 rates.
 Undergrowth, sage and desert brush.
 No timber.

12.50 N. 0° 1' W. bet. secs. 1 and 2.
 Now rough rolling land, ascend
 along spur bearing N. 70° E.
 20.00 Top of ridge, bears N. 80° W. and S. 60° E.
 ; descend
 31.30 ascend.
 29.50 Wash 5 lks. wide course N. 80° E.; asc.
 spur bears N. 80° E. and S. 80° W.
 37.50 Rocky spur, bears N. 80° W. and S. 80° E.
 descend.
 40.00 Set an iron post 3 ft. long,
 1 in. diam., 24 ins. in the
 ground for 1/4 cor. secs. 1 and 2.
 with brass cap miked;

52 1/4 | 51

1912

and raise a mound of stone,
 2 ft. base 1 1/2 ft. high W. of cor.
 44.50 Wash, 5 lks. wide course N. 80° E.
 ascend.
 46.62 Intersect sixth standard parallel N.,
 N. 89° 55' W.; 1.59 Chs. dist. from
 the standard cor. of secs. 35 and 36
 T 31 N., R. 30 E. which is a lava
 rock 3 x 6 x 5 ins. above ground
 marked and witnessed as described
 by the Surveyor General.
 Set an iron post 3 ft. long
 2 in. diam., 24 ins. in the
 ground for closing cor. of