

Subdivision of T. 30 N., R. 30 E.

Chains

37.20

40.05

Top of low hill, descend.
Set an iron post 3 ft. long,
1 in. diam., 24 ins. in the
ground for $\frac{1}{4}$ cor. of secs.
3 and 10, with brass cap mtd.;

53

 $\frac{1}{4}$

510

1912

64.10

80.00

and raise a mound of stone
2 ft. base $1\frac{1}{2}$ ft. high N. of cor.
Wash, 20 lbs. wide, course 575° W.
The cor. of secs. 3, 4, 9 and 10

land, rolling

Soil, gravelly and rocky; 2nd.and 3^d rate

Undergrowth, sage and desert brush.
No timber.

27.10

40.00

$N. 0^\circ 2' W.$ bet. secs. 3 and 4
low rolling land, ascent gradual slope
Wash, 15 lbs. wide, course $5.45^\circ W$; asc.
Set an iron post 3 ft. long,
1 in. diam., 24 ins. in the
ground for $\frac{1}{4}$ cor. of secs 3 and
4, with brass cap mtd.;

54 $\frac{1}{4}$ | 53

1912

46.91

and raise a mound of stone,
2 ft. base $1\frac{1}{2}$ ft. high, W. of cor.
Intersect Sixth Standard Parallel, N., at
 $N. 89^\circ 46' W.$, 1.30 chs. dist. from
the standard cor. of secs. 33
and 34 which is a granite
rock 14 x 8 x 6 ins. above ground,
firmly set, marked and
witnessed as described by
the Surveyor General.
Set an iron post 3 ft. long,