

Subdivision of T. 30 N., R. 30 E.

Chains

47.27

$3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor
Intersect Sixth Standard Parallel, N. at
N. $89^{\circ} 57'$ west, 1.54 chs. dist.;
from the standard cor. of secs.
31 and 32, T. 31 N., R. 30 E. which
is a basalt. rock $5 \times 7 \times 4$ ins. above
ground, firmly set, marked and
witnessed as described by the
Surveyor General.

Set an iron post 3 ft. long,
2 ins., diam., 24 ins. in the
ground for closing cor. of secs.
5 and 6, with brass cap mtd.;

T 31 N R 30 E
531 CC | 532
56 | 55

1912

dig pits, $24 \times 18 \times 12$ ins. crosswise
on each line, E. and W., 3 ft., and
S. of post, 7 ft. dist.; and raise
a mound of earth, 4 ft. base,
2 ft. high. E. of cor.

Land, gently rolling

Soil, sandy loam, 1st rate
undergrowth, sage and desert brush.
no timber

From the closing sec. cor. of
secs. 5 and 6 & run S $89^{\circ} 57' E$

1.54
40.12 on N. side of sec. 5
St. Cor. axis 31 and 32 as described, thence S $89^{\circ} 55' E$
Set an iron post 3 ft. long,
1 in. diam., 24 ins. in the ground
for $\frac{1}{4}$ cor. of sec. 5. with brass
cap mtd.;

55
 $\frac{1}{4}$

1912

and raise a mound of stone
2 ft. base $1\frac{1}{2}$ ft. high S. of cor.