

Resurvey of the South Boundary of T. 33N, R. 30E.

dig pits 24x24x12 ins., in each sec., 6 ft. dist.;
and raise a mound of earth, 4 ft. base,
2 ft. high, N. of cor.

N. 89° 52' W. on S. bdy. sec. 31.

40.00 After diligent search for old $\frac{1}{4}$ sec. cor. of secs.
6 and 31, in this new position, I fail to
find same; therefore I reestablish $\frac{1}{4}$ sec.
cor. for sec. 31 as follows:-

Set a granite stone, 18x9x8 ins., 12 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of sec. 31, marked
 $\frac{1}{4}$ on N. face; dig pits 18x18x12 ins., E. and
W. of stone, 3 ft. dist.; and raise a
mound of earth, 3½ ft. base, 1½ ft. high,
N. of cor.

78.76 Point for cor. of T. 33N, Rs. 29 and 30E,
falls on Placeritas mining dump;
unsuitable for permanent corner.

No topography taken on this resurvey.

Note: I searched diligently for old cor. on the W. bdy. of T. 33N, R. 30E, but was
unable to find any. I therefore set the above $\frac{1}{4}$ sec. cor. as indicated, in agreement with old field notes.

N. 89° 52' W. on N. bdy. sec. 6, T. 32N,
R. 30E.

1.00 Small frame building on line.

1.14 Set a schist stone, 32x10x8 ins., 24 ins.
in the ground, for witness cor. of T. 33
N., Rs. 29 and 30 E., marked R 29 E on
W., R 30 E on E, and W C T 33 N on N.
face, with 6 grooves on E, W, and N.
face; and raise a mound of stone,
2 ft. base, 1½ ft. high, N. of cor.

18.32 Intersect W. bdy. T. 32N, R. 30E., 18 lks.
N. of temp. cor. for T. 32N, Rs. 29 and 30E,
heretofore described.

her
212

At point of intersection,

Set an iron post, 3 ft. long, 3 ins. diam.,
24 ins. in the ground, for ^{being} cor. of T. 32N,
Rs. 29 and 30E., with brass cap mtd.;

