

Subdivision of fracl. T. 27 N., R. 31 E.

Chains July 8, 1912.

Beginning at the cor. of secs. 19 and 30, on the W. bdy. of the township, at 10h., a. m., 1. m. t., I set off $22^{\circ} 29'$ N. on the decl. arc, and $40^{\circ} 11'$ N. on the lat. arc, and determine a meridian with the solar;

Thence I run

East on a random line bet. secs. 19 and 30.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

81.00 Intersect a point 1.60 chs. S. $17'$ E. of cor. of secs. 19, 20, 29 and 30, which is a granite stone, 24 X 14 X 7 ins., marked as described by the surveyor general, and set in a stone mound.

At the point of intersection I set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 19 and 30, with a brass cap, marked

T 27 N R 31 E	
S 19	S 20
cc	
S 30	S 29
1912	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Thence I run

West on a true line bet. secs. 19 and 30.

Over rolling stony land.

25.00 Granite ridge, 30 ft. high, bears N. and S.

25.80 Dry wash, 10 lks. wide, course SE.

40.65 Proportional to the original measurement of the S. bdy. of sec. 30, set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with a brass cap, marked

 $\frac{1}{4}$ S 19

 S 30

1912

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

74.50 Foot of lava hill, bears N. and S. asc. 150 ft.