

Subdivision of T. 30 N., R. 31 E.

Chains.
 40.03 Set an iron post 3 ft. long, 1 in. diam.,
 24 ins. in the ground, for $\frac{1}{4}$ cor.
 of secs. 1 and 12 with brass cap mtd.:

$$\begin{array}{r} 51 \\ \frac{1}{4} \\ \hline 512 \\ 1912 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of C.S.

66.00 Descend gentle slope
 74.75 Wash, 12 lks. wide, course N. 10° W.; asc.

80.06 The cor. of secs. 1, 2, 11 and 12
 Land, mountainous and rolling
 Soil, rocky and gravelly; 3^d rate
 Undergrowth, sage brush
 No timber.

Mountainous land, 40.00 Chains.

8.00 N. 1° W. on a true line bet. secs 1 and 2.
 Over gently rolling land, descending
 Wash, 12 lks. wide, course N. 15° W.

40.00 Set an iron post 3 ft. long,
 1 in. diam., 24 ins. in the
 ground for $\frac{1}{4}$ cor. of secs. 1 and 2
 with brass cap mtd.:

$$\begin{array}{r} 52 \frac{1}{4} \\ \hline 51 \\ 1912 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

50.00 Wash, 10 lks. wide, course N. 10° E

79.90 Intersect sixth standard parallel
 north 2.55 Chains, $589^{\circ} 56'$ E. of
 the old standard cor. of secs. 35
 and 36, T. 31 N., R. 31 E. which is
 a basalt rock 7x7x6 ins. above
 ground, marked and witnessed
 as described by the Surveyor General
 At the point of intersection I
 build a cor. as follows:

Set an iron post 3 ft. long;
 2 ins. diam., 24 ins. in the