

## Subdivisions of T. 30 N., R. 31 E.

Chains

75.00

Wash, 20 lbs. wide, course N. 10° E.

80.10

The cor. of secs. 2, 3, 10, and 11.

Land, rolling

Soil, sandy and gravel loam, 1<sup>st</sup>,  
and 2<sup>nd</sup> rate

Undergrowth sage brush.

No timber.

Sept. 27.

Sept. 24

N. 0° 2' W. on a true line bet.  
secs. 2 and 3.

Over gently rolling land, descending.

32.25

Wash, 20 lbs. wide course N. 20° E.

39.50

Wash, 20 lbs. wide course N 65° W.

40.00

Set an iron post 3 ft. long, 1 in.  
diam., 24 ins. in the ground  
for  $\frac{1}{4}$  cor. of secs. 2 and 3 with  
brass cap mk'd.:53  $\frac{1}{4}$  | 52

1912

and raise a mound of stone,  
2 ft. base 1  $\frac{1}{2}$  ft. high, W. of cor.

53.00

Wash, 30 lbs. wide course N 20° E.

80.00

Intersect sixth standard parallel North  
2.67 Chs. N 89° 50' E. of standard cor.  
of secs. 34 and 35 of T. 31 N. R. 31 E.  
which is a basalt rock 15 x 7  
x 4 ins. above ground, firmly set,  
marked and witnessed as decreed  
by the Surveyor General. At the  
point of intersection I build  
a cor. as follows:Set an iron post 3 ft. long,  
2 ins. diam., 24 ins. in the  
ground for closing cor. of  
secs. 2 and 3. with brass  
cap mk'd.: