

Subdivision of T 30 N., R 31 E

Chains.	
51.00	Wash. 5 lbs. incl. course N 30° W. ascend gradual slope
79.90	The cor. of secs. 4, 5, 8 and 9. Land broken and rolling. Soil, gravelly, 1 st rate undergrowth, sagebrush. No timber
	Set
	N 0° 3' W. on a true line bet. secs. 4 and 5. Over nearly level land, gently descend.
40.00	Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ cor. of secs. 4 and 5 with brass cap inked; $55\frac{1}{4}$ 54 1912
80.00	and raise a mound of stone, 2 ft. base $1\frac{1}{2}$ ft. high, W. of cor. At intersect with standard parallel north. 3.20 chs. 589° 56' E of the standard cor. of secs. 32 and 33, of T 31 N., R 31 E, which is a lava rock 4x3x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. At the point of intersection I build a cor. as follows: Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing cor. of secs. 4 and 5, with brass cap inked; T 31 N R 31 E 532 $533 \cdot CC$ 55 54 1912
	and raise a mound of stone, 2 ft. base $1\frac{1}{2}$ ft. high, S. of cor.